

Advantages of the Allied Ho-Pac®



- Oil splash provides maintenance-free (*no-greasing*) bearing lubrication
- Worry-free “*plug-and-go*” installation
- Four-function valve controls flow, pressure, regeneration and oil flow direction. Prevents damage to the motor and eliminates the need for auxiliary machine mounted hydraulic valves.
- Motor / valve combinations pre-designed for specific Kubota machines
- Mounting designed specifically for Kubota direct pin-on or quick coupler
- Tough-coat hoses prevent cuts and extend wear-life

Ho-Pac® Specifications

Model		300	500	1000
Impulse Force	lbs.	3,000	3,940	8,000
	(n)	(13,340)	(17,530)	(35,586)
Cycles Per Minute		2,000	2,000	2,000
Hydraulic Flow Required	gpm	6/9/14/18 *	9/14/18 *	12/18/21 *
	(lpm)	(23) (34) (53) (68)	(34) (53) (68)	(45) (68) (79)
Maximum Hydraulic Pressure	psi	2,800/2,800/2500/2000	2,000/2,500/2,800	2,000/2,500/2,800
	(bar)	(193) (193) (172) (138)	(138) (172) (193)	(138) (172) (193)
Base Plate Dimensions	in.	12 x 22	12 x 27	24 x 32
	(cm)	(31 x 60)	(31 x 69)	(61 x 81)
Weight	lbs.	305	498	1,053
	(kg)	(138)	(226)	(479)

Kubota Compatibility

Model	300	500	1000
U15	X		
KX41-3	X		
U25S	X		
KX71-3S		X	
KX91-3S		X	
U35S		X	
KX121-3S		X	
U45S		X	X
KX161-3S		X	X
KX080-3			X

* All Ho-Pacs come with proper motor / valve configuration for specific Kubota models



Ho-Pac® Allied's Vibratory Compactor

