

Applications:

- Forestry
- Composting
- Municipal
- Landscaping
- Site-preparation

Functions:

- Slash reduction
- Recreating trails
- Land clearing
- Mulching slash piles
- Tree stump grinding
- Brush cutting
- Orchard pruning
- Grinding material into the soil.



Technical Description:

The FM500HSS is an attachment specifically suited for skid steer loaders. The unit incorporates a powerful and reliable Rexroth hydraulic motor and ready-to-mount hydraulic lines.

Valve specification and pulley configuration can be tailored to suit many skid steer models. The grinding rotor is tipped with carbide hammers, each individually exchangeable. A push-bar enables the FM500HSS to grind standing trees.

For safety considerations, the skid steer operator station should be equipped with a suitable forestry protection package.

Technical Data:

Hydraulic power	60–90 kW	80–120 hp	
Hydraulic flow rate	135–200 l/min @ 200–400 bar	35–52 USgal/min @ 2900–5800 psi	
Working widths	1270 mm	1525 mm	1775 mm
Overall width	1575 mm	1880 mm	2160 mm
Rotor diameter	500 mm	500 mm	500 mm
Weight (approx.)	930 kg	1150 kg	1350 kg

INSIST ON AN AHWI!

Authorised Distributor